



3COM

NBX[®] Feature Codes Guide for Analog Telephones

NBX Networked Telephony Solutions
System Release 6.0

Part Number 900-0339-01
Published June 2006

<http://www.3com.com/>



3Com Corporation
350 Campus Drive
Marlborough, MA
01752-3064

Copyright © 1998–2006, 3Com Corporation. All rights reserved. No part of this documentation may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from 3Com Corporation.

3Com Corporation reserves the right to revise this documentation and to make changes in content from time to time without obligation on the part of 3Com Corporation to provide notification of such revision or change.

3Com Corporation provides this documentation without warranty, term, or condition of any kind, either implied or expressed, including, but not limited to, the implied warranties, terms, or conditions of merchantability, satisfactory quality, and fitness for a particular purpose. 3Com may make improvements or changes in the product(s) and/or the program(s) described in this documentation at any time.

If there is any software on removable media described in this documentation, it is furnished under a license agreement included with the product as a separate document, in the hardcopy documentation, or on the removable media in a directory file named LICENSE.TXT or !LICENSE.TXT. If you are unable to locate a copy, please contact 3Com and a copy will be provided to you.

UNITED STATES GOVERNMENT LEGENDS:

If you are a United States government agency, then this documentation and the software described herein are provided to you subject to the following:

United States Government Legend: All technical data and computer software is commercial in nature and developed solely at private expense. Software is delivered as Commercial Computer Software as defined in DFARS 252.227-7014 (June 1995) or as a commercial item as defined in FAR 2.101(a) and as such is provided with only such rights as are provided in 3Com's standard commercial license for the Software. Technical data is provided with limited rights only as provided in DFAR 252.227-7015 (Nov 1995) or FAR 52.227-14 (June 1987), whichever is applicable. You agree not to remove or deface any portion of any legend provided on any licensed program or documentation contained in, or delivered to you in conjunction with guide.

Unless otherwise indicated, 3Com registered trademarks are registered in the United States and may or may not be registered in other countries.

3Com, the 3Com logo, and NBX are registered trademarks of 3Com Corporation. NBX NetSet is a trademark of 3Com Corporation.

Other brand and product names may be registered trademarks or trademarks of their respective holders.

CONTENTS

ABOUT THIS GUIDE

How to Use This Guide	5
Conventions	6
Documentation	6
Comments on the Documentation	7

1 FEATURE CODES

General Instructions	9
How to Enter a Feature Code	10
NBX Tones That You Hear on Analog Telephones	10
Feature Codes List	12
Paging Codes on the NBX System	21
Paging Codes	21
Paging Zones	22

ABOUT THIS GUIDE

This guide is intended for anyone using an analog telephone on an NBX system. It describes NBX® features that are accessible on analog telephones connected to the NBX system through the Analog Terminal Card or the Analog Terminal Adapter.

On analog telephones, you can use feature codes to access NBX features that are often available on 3Com® Telephones using special buttons.



For best results with feature codes, 3Com recommends that you read through this entire guide before you use the feature code sequences in [Chapter 1](#).

This guide also covers:

- [NBX Tones That You Hear on Analog Telephones](#)
- [Paging Codes on the NBX System](#)



For a full description of the user features on the NBX system, the NBX Voice Mail system, and the NBX NetSet™ administration utility for personal telephone settings, see the NBX Entry Telephone Guide. Ask your administrator how to log in to the NBX NetSet utility.



If the information in the release notes (readme.pdf) on the NBX Resource Pack differs from the information in this guide, follow the instructions in the release notes.

How to Use This Guide

Chapter 1 of this guide describes how to use feature codes and includes a list of the feature codes available from analog telephones on an NBX system. See the *NBX Entry Telephone Guide* for a complete description of those features.

Conventions




[Table 1](#) defines some commonly used words and phrases in this guide.

Table 1 Common Terms

Term	Definition
Auto Attendant	The set of voice prompts that answers incoming calls and describes actions that a caller or user can take to access individual services.
Administrator	The person who is responsible for maintaining your 3Com Networked Telephony Solution.
Receptionist	The person who answers the majority of incoming telephone calls. In some business environments, this person may be a switchboard operator.
User	A person who has a single 3Com Telephone or an analog telephone connected to the NBX system through an ATC card or the single-port ATA device.

[Table 2](#) lists conventions that are used throughout this guide.

Table 2 Icons

Icon	Type	Description
	Information note	Information that describes important features or instructions.
	Caution	Information that alerts you to potential loss of data or potential damage to an application, system, device, or network.
	Warning	Information that alerts you to potential personal injury.

Documentation

The documentation set for 3Com NBX Networked Telephony Solutions is designed to help NBX telephone users, installers, and administrators maximize the full potential of the system.

The *NBX Resource Pack* contains many guides to the NBX products and their related 3Com applications.

When you log in to the NBX NetSet utility as a user, you can view the PDF versions of the *NBX Telephone Guides* and *NBX Feature Codes Guide* by going to **Resources > Phone Guide** and **Feature Code Reference** pages, respectively and clicking their associated links. You can view the *Quick Reference Guide* similarly by clicking the **Telephone Quick**

Reference link. The NBX NetSet utility also includes a searchable Help system with Help buttons on each screen.

Comments on the Documentation

Your suggestions are important to us. They help us to make the NBX documentation more useful to you.

Please send your e-mail comments about this guide or any of the 3Com NBX documentation and Help systems to:

Voice_TechComm_Comments@3com.com

Include the following information with your comments:

- Document title
- Document part number (found on the front or back page)
- Page number



As always, please address all questions regarding the NBX hardware and software to your 3Com NBX Voice-Authorized Partner.

1

FEATURE CODES

This guide describes the NBX feature code sequences and covers these topics:

- [General Instructions](#)
- [How to Enter a Feature Code](#)
- [NBX Tones That You Hear on Analog Telephones](#)
- [Feature Codes List](#)
- [Paging Codes on the NBX System](#)

General Instructions

To access most of these features on an analog telephone, press # or **HF** and enter a 3-digit code.

For a description of the tones that you hear when you use an analog telephone and NBX feature codes, see [“NBX Tones That You Hear on Analog Telephones”](#) later in this chapter.

- In this guide, **HF (“Hook Flash”)** means that, while you are on a call, you press and release the hook switch once. The hook switch is the switch under the handset.



- *Follow these rules for the timing of the **HF**:*
 - *If you press and then release the hook switch too quickly, the system ignores the signal.*
 - *If you press and then hold the hook switch for too long, the system interprets that you have hung up and returns you to dial tone.*
 - *Therefore, press and hold the hook switch for approximately one half second before you release it and move to the next step in the feature code sequence. The length of time that you hold it varies from one analog telephone manufacturer to another.*

- To read the *NBX Entry Telephone Guide* for complete descriptions of the telephone features, log in to the NBX NetSet utility and go to **Resources > Phone Guide** and click the link for Entry Telephone Guide. Then use [Table 3](#) in this chapter to access the features using your analog telephone.

How to Enter a Feature Code

To access NBX features, use the general syntax in [Table 3](#).

To enter a feature code on an analog telephone:

- 1 Pick up the handset.
- 2 Press # (or **HF #** if you are on a call) plus any additional values as specified in [Table 3](#).
- 3 After each step, listen for the appropriate tone as described in [“NBX Tones That You Hear on Analog Telephones”](#) later in this guide.
- 4 Hang up when your call is complete or you have activated the features that you want.



Errors — *If you make an error such as trying to add a fifth party to a conference call or entering an invalid extension or invalid password, you hear the **Error Tone**, which is also known as the “fast busy” or congestion tone. Hang up and start the feature code sequence again.*

NBX Tones That You Hear on Analog Telephones

As you use your analog telephone to receive voice mail and use the feature codes on the NBX system, you hear these tones:

- **Dial Tone** — When you lift the receiver to place a call or begin using one of the features, you hear the normal Dial Tone (except for the circumstance described in the next bulleted item).
- **New Messages Dial Tone** — When your voice mailbox has either new or unsaved messages and you pick up your handset, you hear the New Messages Dial Tone (a repeated short tone, also called the “stutter” tone) until you delete or save every message.
- **Feature Entry Tone** — When you lift the handset and press # (or, when you are already on a call, **HF #**) to begin using one of the features, you hear the Feature Entry Tone, which is a steady sound at a lower pitch than the normal dial tone. You must enter data, for instance, a feature code number, your password, or an extension, as specified in [Table 3](#).

- **Confirmation Tone** — After certain steps, as when you add a party to a conference call, you hear a short Confirmation Tone or “beep,” which confirms that you have completed the action.
- **Error Tone** — On *any* telephone, you hear the “fast busy” tone, also called the “congestion” tone, when no circuits are available. In addition, on analog telephones that are connected to the NBX system, you hear the “fast busy” tone if you make an error such as trying to enter an unsupported feature code, an invalid extension, or an invalid password. Hang up and start the feature code sequence again.
- **Feature Active Tone** — Example: You activate one of the “persistent” features, for instance, you lock your telephone, and then hang up. The next time that you pick up the handset on your analog telephone, you hear the Feature Active Tone. This pair of tones, a sound followed by a higher sound, is repeated to remind you that you have enabled one of these features:
 - Caller ID Restriction — All
 - Do Not Disturb
 - Forward All Calls to Voice Mail (that is, to your call coverage point)
 - Lock or Unlock Your Telephone
 - Call Forward All
 - Call Forward Busy
 - Call Forward No Answer

These features are “persistent,” that is, each one remains active until you turn it off, as described in [Table 3](#).

If you forget which of the persistent features you have activated on your analog telephone, log in to the NBX NetSet utility and go to **My Calling Privileges > Feature Settings**. See the NBX Telephone Guides for information on how to log in to the NBX NetSet utility.



Exception: If you have activated one or more persistent features *and* your mailbox has messages, you hear the New Messages Dial Tone whenever you pick up the handset until you have deleted all messages.

Feature Codes List

Use the directions in [“How to Enter a Feature Code”](#) earlier in this guide to access NBX features from any analog telephone on the NBX system using the feature codes in [Table 3](#).



Errors — *If you make an error such as trying to add a fifth party to a conference call or entering an invalid extension or invalid password, you hear the **Error Tone**, which is also known as the “fast busy” or congestion tone. Hang up and start the feature code sequence again.*

Table 3 NBX Feature Codes from Analog Telephones

Features	Using Codes
Account Codes	
Allow the system to rack the next call that you make.	# (Feature Entry Tone)
Log in to the NBX NetSet utility and go to Directory > Account Codes for a list of public account codes or see your administrator. The Call Reports application tracks the calls.	+ 888 (Feature Entry Tone) + account code + #
On an analog telephone, you can use this code sequence only before you make the call. You cannot use it for incoming calls to analog telephones.	(Confirmation Tone) + telephone number
ACD Groups, Hunt Groups, and Calling Groups	
Log in to or out of an ACD group, dynamic hunt group, or calling group of which you are a member.	# (Feature Entry Tone) + feature code for the group
Your administrator must first map the group extension to a Feature Code and assign a group password.	(Feature Entry Tone) + group password + #
To view the groups to which you belong, log in to the NBX NetSet utility and go to Group Membership > ACD Groups or Hunt Groups and the related Help topics. You can also use these screens to log into or out of these groups.	(Confirmation Tone) To log out, repeat the sequence.
Automatic Callback	
While on a call to an NBX extension that is in use or unanswered, use this feature to request a call back ring. The NBX system then automatically attempts to connect you when the called party at this extension becomes available.	# (Feature Entry Tone) + 469 (Confirmation Tone) + hang up

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
Call Forward All	
Forward all incoming calls to your specific call coverage point regardless of the state of your phone.	# (Feature Entry Tone)
When you specify an external telephone number as the destination, start by entering 9 or 8 or whatever is required to access an outside line. Enter a * if a pause is required between an access code and a destination number.	+ 465 (Feature Entry Tone) + the destination to forward calls to + # (Confirmation Tone) + hang up
	Persists until you turn off the feature by repeating # + 465 + hang up.
Call Forward Busy	
Forward all calls to your call coverage point when your phone is busy.	# (Feature Entry Tone)
When you specify an external telephone number as the destination, start by entering 9 or 8 or whatever is required to access an outside line. Enter a * if a pause is required between an access code and a destination number.	+ 467 (Feature Entry Tone) + the destination to forward calls to + # (Confirmation Tone) + hang up
	Persists until you turn off the feature by repeating # + 467 + hang up.
Call Forward No Answer	
Forward all calls to your call coverage point when your phone rings for a specified number of rings.	# (Feature Entry Tone)
To specify the number of rings before the call is forwarded, log in to the NBX NetSet utility and go to Call Forward > Call Forward . The default is 4.	+ 466 (Feature Entry Tone) + the destination to forward calls to + # (Confirmation Tone) + hang up
When you specify an external telephone number as the destination, start by entering 9 or 8 or whatever required to access an outside line. Enter a * if a pause is required between an access code and a destination number.	Persists until you turn off the feature by repeating # + 466 + hang up.

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
Call Park — Park a Call	
Place a call on hold so that it can be picked up from another extension on your NBX system.	Make or receive a call + HF
Confirm these default Call Park extension ranges with your administrator, who can set different extensions:	+ # (Feature Entry Tone)
■ 4-digit dial plan: 6000 to 6099	+ 444
■ 3-digit dial plan: 601 to 609	+ one of the Call Park extensions for your NBX system (Confirmation Tone)
If the Call Park extension that you chose is busy, you hear an Error Tone or, if you have hung up, the call returns to your phone with a ring. Repeat the sequence with another Call Park extension.	
Call Park — Retrieve a Call	
Pick up a call that has been parked.	Extension where the call was parked (Do not press HF # .)
Call Pickup — Directed	
Pick up a call that is ringing on another user's telephone. Your telephone and the ringing telephone must be members of the same call pickup group, or the ringing telephone's pickup group must allow pickup from telephones that are not members of the group.	# (Feature Entry Tone) + 455 (Feature Entry Tone) + the extension of the ringing telephone
Call Pickup — Group	
From your telephone, pick up calls that are ringing on another telephone in your group.	# (Feature Entry Tone)
Your system administrator assigns call pickup group numbers in these ranges:	+ 456 (Feature Entry Tone)
4-digit dial plan: 482 – 531	+ call pickup group number (Confirmation Tone)
3-digit dial plan: 500 – 531	
Call Privacy — On/Off	
Toggle Call Privacy on and off to block or accept supervisory monitoring on a call-by-call basis.	# (Feature Entry Tone)
If your administrator has assigned you to a CoS group that allows Call Privacy, you can activate this feature before a call (for example, by going off-hook and dialing Feature code 428 and then dialing an internal or external call), or during a call (for example, dialing Feature code 428 after answering an incoming call).	+ 428 (Confirmation Tone)

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
Call Toggle	
<p>Toggle between two calls.</p> <p>If your line or system has Call Waiting service, use Flash, as described later in this table.</p>	<p>Not supported for analog telephones. Use Call Park or, in some cases, Flash. (See Flash, later in this table, to determine when the Flash function can toggle between two calls.)</p>
Camp On — Direct	
<p>While on an active call, you can initiate Camp On to directly queue the call on to an NBX destination extension that is in use or busy. (You cannot invoke Camp On as part of a call transfer from an analog device.) When the destination extension becomes available, the system automatically rings that extension.</p>	<p>HF # (Feature Entry Tone) +468 (Feature Entry Tone) (+ destination extension) (Confirmation Tone)</p>
Caller ID Restriction (CLIR — All) — On/Off	
<p>Restrict the NBX system from sending out your Caller ID information for all calls.</p> <p>To view your current setting, log in to the NBX NetSet utility and go to My Calling Privileges > Feature Settings.</p>	<p># (Feature Entry Tone) + 889 (Confirmation Tone) + hang up</p> <p>Persists until you turn off the feature by repeating the sequence.</p>
Caller ID Restriction (CLIR — Next Call)	
<p>Restrict the NBX system from sending out your Caller ID information for only this call.</p>	<p># (Feature Entry Tone) + 890 (Confirmation Tone) (Dial Tone) + outside party's number</p>
Class of Service Override	
<p>Apply the features and calling permissions of your own telephone to another telephone on the NBX system for only this call.</p>	<p># (Feature Entry Tone) + 433 (Feature Entry Tone) + your own extension + # (Feature Entry Tone) + your password + # (Confirmation Tone) (Dial Tone) + the outside party's number</p>

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
Conference Call — Add	
<p>Add one caller to an already-established phone call.</p> <p>To add a fourth party (if 4-party conferencing is supported), repeat the sequence. You cannot add a fifth party or a voice mailbox to a conference.</p>	<p>Make or receive a call</p> <p>+ HF (Dial Tone)</p> <p>+ extension or telephone number or speed dial (speak to the party)</p> <p>+ HF (Confirmation Tone)</p> <p>(Three parties are now on the call)</p>
Conference Call — Drop	
<p>Drop the last caller that you added to a conference call.</p> <p>To return to the remaining parties in the conference call, HF. Only the person who added the last party can drop that party.</p>	<p>HF (Dial Tone)</p> <p>+ # (Feature Entry Tone)</p> <p>+ 431 (Confirmation Tone)</p>
Direct Mail Transfer	
<p>Transfer a call directly to another person's voice mailbox on your NBX system.</p> <p>The call is transferred when you hang up.</p>	<p>Make or receive a call</p> <p>+ HF (Dial Tone)</p> <p>+ # (Feature Entry Tone)</p> <p>+ 441 (Feature Entry Tone)</p> <p>+ other person's extension (Confirmation Tone)</p> <p>+ hang up</p>
Do Not Disturb — On/Off	
<p>Send all incoming calls directly to the call coverage point that you specified in the NBX NetSet utility</p> <p>Call Forward > Call Forward or Override.</p> <p>To view the current setting, log in to the NBX NetSet utility and go to My Calling Privileges > Feature Settings.</p>	<p># (Feature Entry Tone)</p> <p>+ 446 (Confirmation Tone)</p> <p>Persists until you turn off the feature by repeating the sequence.</p>
Extend Wrap-Up Time	
<p>Extend the ACD Wrap-Up Time session duration (by another quantum of the wrap-up time duration). This feature is only valid if you are already in the wrap-up mode. You can use this feature only once per call.</p>	<p># (Feature Entry Tone)</p> <p>+ 973 (Confirmation Tone)</p>

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
Flash	
<p>If your NBX system is connected to a Central Office by one or more Analog Line Card ports, and if the CO provides your organization with a feature such as Call Waiting that requires a flash signal, use this sequence to signal the CO to put the existing call on hold and toggle to the call that is waiting.</p> <p>Ask your administrator if any of the lines on your telephone has this Call Waiting feature.</p>	<p>HF (Dial Tone) + # (Feature Entry Tone) + 260</p> <p>To return to the first call, repeat the sequence.</p>
Forward All Calls to Voice Mail — On/Off	
<p>Send all incoming calls to your voice mailbox (or to wherever you have specified as your call coverage point) after one ring on your telephone.</p> <p>To view the current setting, log in to the NBX NetSet utility and go to My Calling Privileges > Feature Settings.</p>	<p># (Feature Entry Tone) + 440 (Confirmation Tone)</p> <p>Persists until you turn off the feature by repeating the sequence.</p>
Hold	
<p>Place a telephone call on hold.</p>	<p>HF (Dial Tone)</p> <p>Do not hang up. To return to the call on hold, press HF again.</p>
Lock Your Telephone — On/Off	
<p>Prevent others from dialing unauthorized telephone calls from your telephone.</p> <p>To view the current setting, log in to the NBX NetSet utility and go to My Calling Privileges > Feature Settings.</p>	<p># (Feature Entry Tone) + 432 (Feature Entry Tone) + password + # (Confirmation Tone)</p> <p>Persists until you turn off the feature by repeating the sequence.</p>
Message Waiting Indicator to Telephone — Send	
<p>Light a status button, a Message Waiting Indicator (MWI), next to a programmable access button and leave a call back number on another telephone.</p> <p>Your administrator must first map a button on an NBX Telephone that can receive an MWI message.</p> <p>An analog telephone can send or cancel an MWI but not receive one.</p>	<p># (Feature Entry Tone) + 412 (Feature Entry Tone) + extension to receive MWI + # (Confirmation Tone)</p>

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
Message Waiting Indicator to Telephone — Cancel	
Cancel a Message Waiting Indicator (MWI) that you have sent. Cancel removes the message from the destination telephone's list and, if it is the only unattended MWI on that telephone, it turns off the MWI light.	# (Feature Entry Tone)
You can cancel only from the same telephone from which you sent the MWI message.	+ 413 (Feature Entry Tone)
An analog telephone can send or cancel an MWI but not receive one.	+ extension that received MWI + # (Confirmation Tone)
Messages	
Listen to, save, and delete your NBX voice messages.	500 **
If your system uses a voice messaging application other than NBX Messaging, see the documentation for the application.	+ your extension + password + #
Log in to the NBX NetSet utility and go to Resources > Phone Guide for a description of NBX Messaging.	
Password — Set Initially	
If your system uses NBX Voice Messaging , follow the NBX voice prompts to set your NBX NetSet and voice mail password.	500 ** and follow the voice prompts
If your system uses a voice messaging application other than NBX Voice Messaging , use this code sequence to set your password for the NBX NetSet utility. 3Com recommends that you use the same password for the NBX NetSet utility and your messaging application.	<i>OR</i> , for systems that do not use NBX Messaging: # (Feature Entry Tone)
FOR ALL VOICE MESSAGING SYSTEMS:	+ 434 (Feature Entry Tone)
■ Use only 4- to 10-digit numbers	+ new password
■ Do not use letters, *, or # as part of your password.	+ # (Feature Entry Tone)
	+ repeat your new password + # (Confirmation Tone)

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
Password — Change	
<p>If your system uses NBX Voice Messaging, follow the NBX voice prompts to change your NBX password (which changes your NBX NetSet password, because they are the same) or use the NBX NetSet utility.</p>	<p>500 ** + current password + # + 2 + follow the prompts</p>
<p>If your system uses a voice messaging application other than NBX Voice Messaging, use this code sequence to change your password for the NBX NetSet utility. 3Com recommends that you use the same password for the NBX NetSet utility and your messaging application.</p>	<p>OR, for systems that do not use NBX Voice Messaging:</p>
FOR ALL VOICE MESSAGING SYSTEMS:	
<ul style="list-style-type: none"> ■ If you forget your password, the administrator can reset it to your extension. Then use this code sequence. 	<p># (Feature Entry Tone) + 434 (Feature Entry Tone) + current password + # (Feature Entry Tone) + new password + # (Feature Entry Tone) + repeat your new password + # (Confirmation Tone)</p>
Pulse to Tone	
<p>Switch from pulse dialing to tone dialing while you are on a call. Persists only for the current call.</p>	<p>Receive a call + HF (Dial Tone) + # (Feature Entry Tone) + 891 (Confirmation Tone)</p>
Redial	
<p>Redial the last number that was called on this telephone.</p>	<p># (Feature Entry Tone) + 401</p>
Release	
<p>Disconnect a call.</p>	<p>HF (Dial Tone) + # (Feature Entry Tone) + 111</p>

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
<p>Speed Dial — Personal List</p> <p>Dial a party to whose number you have given a personal speed dial number. Range: 601 – 699</p> <p>You can assign and print out your speed dial numbers by logging in to the NBX Netset utility and going to Directory > Personal Speed Dial.</p>	<p># (Feature Entry Tone) + personal speed dial number</p>
<p>Speed Dial — System-Wide List</p> <p>Dial one of the system-wide speed dial numbers that have been assigned by the administrator.</p> <p>Range: 700 – 799</p> <p>You can view and print out the system-wide speed dial numbers by logging in to the NBX Netset utility and going to Directory > System-Wide Speed Dial.</p>	<p># (Feature Entry Tone) + system-wide speed dial number</p>
<p>Transfer</p> <p>Transfer a call to an internal extension or an external telephone number.</p> <p>Announced or Screened Transfer</p> <p>Stay on the line to announce the call and then hang up.</p> <p>Unannounced or Blind Transfer</p> <p>After you dial the number, hang up.</p> <p>The call is not transferred until you hang up.</p> <p>You can combine this sequence with the sequence for Speed Dial – Personal or Speed Dial – System-Wide.</p>	<p>HF (Dial Tone) + extension, telephone number, or speed dial number + hang up</p>
<p>WhisperPage</p> <p>Use WhisperPage to dial an NBX extension that is involved in an active conversation with another person and speak to that person without the other party on the call being able to hear you.</p> <p>You and the person acting as a listener in a WhisperPage session must be assigned to an NBX WhisperPage domain and have appropriate access privileges.</p> <p>To view your WhisperPage access privileges, log in to the NBX NetSet Utility and go to System Group Settings > WhisperPage.</p> <p>The WhisperPage listener can block or end a WhisperPage session by activating Do Not Disturb.</p>	<p># (Feature Entry Tone) +426 (Feature Entry Tone) (+ destination extension) (After a 0 to 9.9 second delay, Confirmation Tone) (Begin whispering)</p>

Table 3 NBX Feature Codes from Analog Telephones (continued)

Features	Using Codes
Wrap-Up Time	
Activate the ACD Wrap-Up Time session if this feature has been enabled by the ACD administrator. You can extend the Wrap-Up Time session duration by using the Extend Wrap-up Time feature.	# (Feature Entry Tone) + 972 (Confirmation Tone)

Paging Codes on the NBX System

There are two different methods to broadcast a message through audio speakers: paging to all extensions, and paging to zones (specified subsets of all extensions). Each method allows you to broadcast a message to different destinations, depending on your location and equipment.

Paging Codes

System-wide paging allows you to broadcast a message to all internal extensions, to a Public Address system, or both simultaneously. Paging codes, as described in [Table 4](#), have default values for each destination.

Table 4 Paging Codes

Feature	3-digit dial plan (default codes)	4-digit dial plan (default codes)
External Paging	620	6200
Broadcast an announcement over a public address system that has a paging amplifier and speaker system that is connected to your NBX system.		
Internal Paging	621	6201
Broadcast an announcement through the speakers on all 3Com® Business Telephones on your system except those that have been set to Do Not Disturb.		
Simultaneous Paging	622	6202
Broadcast an announcement externally and internally at the same time.		

To page all internal extensions, or an external extension, or both, perform the following steps:

- 1 Pick up the handset.
- 2 Dial the appropriate paging code on your system.

- 3 Speak the broadcast message into your handset.
- 4 Hang up.

Paging Zones A page zone is a subset of all internal extensions to which you can direct a broadcast using a preconfigured extension. You can include a P.A. system in the page, or you can page both the zone and the P.A. system simultaneously. Zone extensions are configured by your administrator.

To discover the zone page extensions for your system:

- 1 Log in to the NBX NetSet utility.
- 2 Go to **System Group Settings > Page Zones**.
- 3 View the existing page zones and their extension numbers.
- 4 In the Extension column, click an extension number to display the list of members for that zone.



You can view zone memberships only if the administrator authorizes you to do so.

To page all internal extensions, or an external extension, or both, perform the following steps:

- 1 Pick up the handset.
- 2 Dial the appropriate paging extension for your zone.
- 3 Speak the broadcast message into your handset.
- 4 Hang up.



Cordless telephones and analog telephones can initiate a zone page, but cannot receive a zone page.